

View Online at <https://aerobasegroup.com/nsn/5930-00-848-7475>

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

5.250 inches

Overall Height:

6.000 inches

Overall Width:

3.500 inches

Longest Horizontal Distance Between Mounting Centers:

2.562 inches

Longest Vertical Distance Between Mounting Centers:

3.500 inches

Pressure Switch Type:

Gage

Mounting Method:

Flush and threaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

20 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

10.0 amperes resistive load second voltage and 10.0 amperes inductive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+300.00/+3000.00 actuation point pounds per square inch and +200.00/+2700.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Voltage Rating In Volts:

450.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A048b0