

View Online at <https://aerobasegroup.com/nsn/5930-00-849-0418>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Body Diameter:**

1.500 inches

**Bushing Length:**

0.320 inches

**Body Length:**

2.390 inches

**Actuator Length:**

1.500 inches

**Actuator Style:**

Roller arm

**Actuator Roller Diameter:**

0.750 inches

**Actuator Roller Width:**

0.310 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

144.0 inch-ounces

**Switch Actuating Force:**

400.0 inch-ounces

**Actuator Movement:**

13.0 pretravel degrees and 45.0 overtravel degrees and 6.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0