

View Online at <https://aerobasegroup.com/nsn/5930-00-849-1382>

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.998 inches and 1.002 inches

Body Length:

Between 1.925 inches and 1.955 inches

Body Width:

Between 0.677 inches and 0.697 inches

Body Height:

Between 1.035 inches and 1.065 inches

Unthreaded Mounting Hole Diameter:

Between 0.139 inches and 0.142 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.890 inches and 0.999 inches

Actuator Height:

Between 0.030 inches and 0.040 inches

Actuator Free Position Height:

Between 0.610 inches and 0.640 inches

Actuator Adapter Style:

Pushbutton

Adapter Bushing Length:

Between 0.675 inches and 0.705 inches

Maximum Voltage Rating In Volts:

250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, double break, momentary action, with contact on arm. Single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 16.0 ounces and 32.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.188 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

600.000 milliamperes resistive dc and 400.000 milliamperes inductive dc and 600.000 milliamperes lamp dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0