NSN 5930-00-849-3683

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-849-3683

| Hazardous Locations/environmental Protection: |
|---|
| Dustproof |
| Overall Length: |
| 1.250 inches |
| Overall Height: |
| 0.440 inches |
| Overall Width: |
| 0.401 inches |
| Mounting Slot Width: |
| 0.125 inches |
| Body Length: |
| 0.776 inches |
| Body Width: |
| 0.375 inches |
| Body Height: |
| 0.251 inches |
| Distance Between Mounting Facility Centers: |
| 1.000 inches |
| Tempurature Sensing Element Type: |
| Expanding shell |
| Operating Tempurature Rating: |
| Between -65.0 degrees fahrenheit and 220.0 degrees fahrenheit |
| Mounting Method: |
| Clip and slot |
| Features Provided: |
| Hermetically sealed case |
| Contact Action Stimulus: |
| Increase |
| Mounting Facility Pattern: |
| Two position in-line |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally closed, momentary action |
| Terminal Type: |
| Tab, solder lug |
| Contact Load Current Rating: |
| 2.5 amperes resistive load first voltage |
| Contact Adjustability: |
| Actuation point adjustable, preset |
| Contact Adjustment Range: |
| -20.00/+200.00 actuation point degrees fahrenheit |

Contact Adjustment Type:

Internal actuation point screw

NSN 5930-00-849-3683

Thermostatic Switch - Page 2 of 2



Contact Stimulus Rating:

120.00 actuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0