NSN 5930-00-849-4908

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-849-4908 **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Watertight **Overall Length:** 2.770 inches **Overall Height:** 1.500 inches **Overall Width:** 1.500 inches **Body Diameter:** Between 1.485 inches and 1.515 inches **Bushing Length:** 1.000 inches **Body Length:** 1.395 inches **Actuator Diameter:** Between 0.245 inches and 0.255 inches **Actuator Height:** 0.375 inches **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.625 inches **Nonpile-up Contact Arrangement:** 1 pole, single throw, both positions maintained single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 15.000 amperes resistive dc and 10.000 amperes inductive dc and 1.000 amperes resistive ac and 5.000 milliamperes inductive ac and 1.000 amperes motor ac **Thread Series Designator:**

Unef

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

NSN 5930-00-849-4908

Push Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0