

View Online at <https://aerobasegroup.com/nsn/5930-00-852-2565>

Overall Length:

9.000 inches

Power Cable Length:

24.000 inches

Ac Voltage Rating:

230.000 volts

Frequency Rating:

60.000 hertz

Overall Diameter:

1.250 inches

Actuation Method:

Buoyancy

Electrical Connection Type:

Cable

Internal Battery Accommodation:

Not included

Current Rating At Maximum Rated Voltage:

10.0 amperes resistive load

Float Quantity:

1

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 125.0 degrees fahrenheit

Mounting Method:

Thread

Mounting Position:

Vertical to 45 degrees angle mtg position

Contact Arrangement:

Spst normally open

Relay:

Not included

Liquid Type For Which Designed:

Lubricating oil

Float Effective Travel:

0.250 inches

Mounting Dimensions:

Mtg by 1-1/4 in. Npt thd connection

Tank Insertion Length:

8.000 inches

Extra Long Reference Number:

Ls-800-2-ss-bn-spst-100-gr1-1, lo=8.75-l1=6.75nc, c

Phase:

Single

Special Features:

Float is reversible on stem to select normally open or normally closed position

Fsc Application Data:

Switch, float, liquid level, except engine

Reference Number Differentiating Characteristics:

As differentiated by operating temp rating, float quantity, mounting method and tank insertion length

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

T109-d