

View Online at <https://aerobasegroup.com/nsn/5930-00-852-6681>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Submersible

**Overall Length:**

1.346 inches

**Overall Height:**

2.590 inches

**Overall Width:**

1.680 inches

**Bushing Length:**

Between 0.460 inches and 0.480 inches

**Body Length:**

1.346 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.235 inches and 0.245 inches

**Actuator Height:**

Between 0.660 inches and 0.720 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Actuator Position-locking Relationship:**

Up position locked in and down position locked in

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes resistive dc and 12.000 amperes inductive dc and 5.000 amperes lamp dc and 20.000 amperes resistive ac and 15.000 amperes inductive ac and 4.000 amperes lamp ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 screw

**Reference Number Differentiating Characteristics:**

Bright chrome finish on dress nut and actuator

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0