## NSN 5930-00-853-1943

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-853-1943

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Body Length:
0.850 inches
Body Width:
0.265 inches
Body Height:
0.359 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Round
Actuator Diameter:
0.092 inches
Actuator Height:
0.100 inches
Actuator Free Position Height:
0.100 inches
Maximum Voltage Rating In Volts:
200.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
1.0 ounces
Switch Actuating Force:
5.0 ounces
Actuator Movement:
0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac
Special Features:
Terminals enclosed in potting compound
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a

## NSN 5930-00-853-1943

Sensitive Switch - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A053a0