## NSN 5930-00-853-1943

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-853-1943

## Body Style:

Hole mounted

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

## Body Length:

0.850 inches

#### **Body Width:**

0.265 inches

## **Body Height:**

0.359 inches

#### **Unthreaded Mounting Hole Diameter:**

0.088 inches

#### **Actuator Style:**

Round

#### Actuator Diameter:

0.092 inches

## Actuator Height:

0.100 inches

#### **Actuator Free Position Height:**

0.100 inches

## Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

#### Inclosure Type:

Fully enclosed

## **Mounting Method:**

Unthreaded hole

#### Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

#### Switch Release Force:

1.0 ounces

#### Switch Actuating Force:

5.0 ounces

#### **Actuator Movement:**

0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

#### Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

#### **Special Features:**

Terminals enclosed in potting compound

## **Terminal Type And Quantity:**

2 wire lead

#### Shelf Life:

N/a

# NSN 5930-00-853-1943

Sensitive Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

