

View Online at <https://aerobasegroup.com/nsn/5930-00-853-7386>

**Body Style:**

Hole mounted

**Overall Length:**

2.422 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.998 inches and 1.002 inches

**Body Length:**

Between 1.922 inches and 1.952 inches

**Body Width:**

Between 0.662 inches and 0.702 inches

**Body Height:**

0.984 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.139 inches and 0.143 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

Between 1.062 inches and 1.188 inches

**Actuator Roller Diameter:**

Between 0.360 inches and 0.390 inches

**Actuator Roller Width:**

Between 0.135 inches and 0.165 inches

**Actuator Adapter Style:**

Roller arm

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

0.5 ounces

**Switch Actuating Force:**

6.0 ounces

**Actuator Movement:**

Between 0.188 pretravel inches and 0.031 overtravel inches and 0.050 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 1.000 amperes inductive dc and 1.500 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 1.500 amperes lamp ac

**Test Data Document:**

81349-mils8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0