

View Online at <https://aerobasegroup.com/nsn/5930-00-854-2529>

Thread Length:

0.440 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof and explosion proof

First Flat Length:

0.468 inches single actuator

Flat Height:

0.210 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.115 inches single actuator

Individual Section Quantity:

7

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

5 each section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks 5th section front

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Special Features:

Fungus proof

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0