

View Online at <https://aerobasegroup.com/nsn/5930-00-854-8291>

Thread Class:

2b single pressure connection

Inside Diameter:

0.438 inches single connection

Thread Length:

0.454 inches single pressure connection

Hazardous Locations/environmental Protection:

Dustproof and watertight

Overall Length:

5.000 inches

Overall Height:

5.688 inches

Overall Width:

2.688 inches

Body Height:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Longest Horizontal Distance Between Mounting Centers:

2.406 inches

Shortest Horizontal Distance Between Mounting Centers:

0.656 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

400.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes inductive load third voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+60.00/+350.00 actuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level fourth voltage

Pressure Connector Type:

Gasket seal, threaded internal single connection

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0