

View Online at <https://aerobasegroup.com/nsn/5930-00-855-1649>

Body Style:

Hole mounted

Overall Length:

Between 0.771 inches and 0.791 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Overall Height:

Between 0.514 inches and 0.547 inches

Overall Width:

Between 0.247 inches and 0.253 inches

Body Length:

Between 0.771 inches and 0.791 inches

Body Width:

Between 0.247 inches and 0.253 inches

Body Height:

Between 0.346 inches and 0.366 inches

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.110 inches

Actuator Style:

Leaf

Actuator Width:

0.125 inches

Actuator Free Position Height:

Between 0.337 inches and 0.350 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

Switch Release Force:

0.5 ounces

Switch Actuating Force:

4.0 ounces

Actuator Movement:

Between 0.075 pretravel inches and 0.031 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 5.000 amperes resistive ac

Terminal Type And Quantity:

3 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0