

View Online at <https://aerobasegroup.com/nsn/5930-00-855-3431>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.530 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

6.720 inches

**Overall Height:**

1.310 inches

**Overall Width:**

1.120 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.909 inches single actuator and 0.911 inches single actuator

**Nonturn Device Radius:**

0.380 inches at 3: 00 o'clock

**Individual Section Quantity:**

7

**Nonturn Device Type:**

Tab at 3: 00 o'clock

**Operating Temperature Range:**

-65.0/+125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

9 each section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

9 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

**Style Designator:**

Tap, square frame

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0