Flow Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-855-3651

	Locations/environmental Protection:
Vibration res	sistant
Overall Len	gth:
4.438 inches	
Overall Heig	ght:
5.000 inches	3
Operating T	empurature Rating:
Between -65	5.0 degrees fahrenheit and 250.0 degrees fahrenheit
Mounting N	lethod:
Line and three	eaded bushing
Features Pr	ovided:
Hermetically	sealed case
Thready Qt	y Per Inch (tpi):
14 single thr	eaded bushing
Contact Act	tion Stimulus:
Decrease	
Thread Size	
0.500 inches	s single threaded bushing
Nonpile-up	Contact Arrangement:
1 pole, sing	le throw, normally closed, momentary action
Terminal Ty	/pe:
Wire lead	
Contact Loa	ad Current Rating:
45.4 milliam	peres resistive load first voltage
Contact Ad	justability:
Deactuation	point not adjustable
Contact Sti	mulus Rating:
25.00 deact	uation point gallons per minute
Contact Vo	Itage Rating In Volts:
32.0 dc at se	ea level second voltage
Media For V	Vhich Designed:
Liquid	
Thread Seri	es Designator:
Npt single th	readed bushing
Shelf Life:	
N/a	
Unit Of Mea	Isure:
Demilitariza	ition:
No	
Fiig:	
-	