

View Online at <https://aerobasegroup.com/nsn/5930-00-855-3938>

Overall Length:

2.020 inches

Outside Diameter:

0.125 inches single connection

Body Diameter:

1.437 inches

Body Length:

0.750 inches

Overall Diameter:

1.690 inches

Pressure Switch Type:

Gage

Mounting Method:

Inlet connection

Thready Qty Per Inch (tpi):

27 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

150.00 pounds per square inch

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 two circuit, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

8.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+1.00/+7.00 actuation point pounds per square inch and +1.00/+7.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Stimulus Rating:

4.00 actuation point pounds per square inch and 3.00 deactuation point pounds per square inch and 1.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

6.0 dc at sea level first voltage

Pressure Connector Type:

Flared, threaded external single connection

Special Features:

Plastic coated, weather-proofed housing

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Ptf-sae short single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A048b0