

View Online at <https://aerobasegroup.com/nsn/5930-00-855-3938>

**Overall Length:**

2.020 inches

**Outside Diameter:**

0.125 inches single connection

**Body Diameter:**

1.437 inches

**Body Length:**

0.750 inches

**Overall Diameter:**

1.690 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Inlet connection

**Thready Qty Per Inch (tpi):**

27 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

150.00 pounds per square inch

**Thread Size:**

0.125 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 two circuit, one position momentary

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

8.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+1.00/+7.00 actuation point pounds per square inch and +1.00/+7.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

Internal deactuation point screw and internal actuation point screw

**Contact Stimulus Rating:**

4.00 actuation point pounds per square inch and 3.00 deactuation point pounds per square inch and 1.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

6.0 dc at sea level first voltage

**Pressure Connector Type:**

Flared, threaded external single connection

**Special Features:**

Plastic coated, weather-proofed housing

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Ptf-sae short single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0