# NSN 5930-00-855-4049

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-855-4049

#### **Thread Class:**

2b single mounting facility

### Hazardous Locations/environmental Protection:

Dustproof

## **Overall Length:**

4.875 inches

#### **Overall Height:**

4.125 inches

#### **Overall Width:**

4.125 inches

#### First Flat Length:

0.750 inches single actuator

#### Flat Height:

0.219 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

1.000 inches single actuator

#### Individual Section Quantity:

6

#### Knob Manufacturer Code:

82121

#### Knob Manufacturer Part Number:

А

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

1 each section front

#### **Throw Quantity:**

1 each section front

#### Mounting Facility Circle Radius:

1.620 inches single mounting facility

#### **Mounting Method:**

Threaded hole single mounting facility

#### Features Provided:

Actuator knob

#### Thready Qty Per Inch (tpi):

20 single mounting facility

### Thread Size:

0.250 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

500.0 ac at sea level

# NSN 5930-00-855-4049

Rotary Switch - Page 2 of 2



# **Mounting Facility Pattern:** Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round, flatted, threaded hole single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes each section front **Switch Actuator Positioning Increment:** 90.0 degrees single actuator Switch Actuator Stop Device Type: Adjustable stop single actuator **Contact Load Current Rating:** 30.0 amperes resistive load ac at sea level Style Designator: Tap, circuit selector **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A052b0