## NSN 5930-00-855-4062

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-855-4062

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
6.250 inches
Overall Height:
6.000 inches
Overall Width:
4.750 inches
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
1.750 inches single actuator
Unthreaded Mounting Hole Diameter:
0.406 inches single mounting facility and 0.410 inches single mounting facility
Individual Section Quantity:
2
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
105605a-2a
Longest Horizontal Distance Between Mounting Centers:
3.781 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
3.781 inches single mounting facility
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
2 each section front
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
500.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:

4 single actuator

## **NSN 5930-00-855-4062** Rotary Switch - Page 2 of 2



Shaft Type:
Round single actuator
Terminal Type:
Tab, solder lug
<b>Contact Switching Action:</b>
Breaks before makes each section front
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
60.0 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A052b0