NSN 5930-00-855-4103

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-855-4103

Overall Length:
0.969 inches
Overall Height:
Between 0.334 inches and 0.364 inches
Body Diameter:
0.578 inches
Body Height:
Between 0.329 inches and 0.350 inches
Unthreaded Mounting Hole Diameter:
Between 0.135 inches and 0.140 inches
Distance Between Mounting Facility Centers:
0.938 inches
Tempurature Sensing Element Type:
Internal sensor
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action
1 pole, single throw, normally closed, momentary action
1 pole, single throw, normally closed, momentary action Terminal Type:
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating:
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 8.3 amperes resistive load second voltage Contact Adjustability:
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 8.3 amperes resistive load second voltage
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 8.3 amperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 8.3 amperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 35.00 actuation point degrees fahrenheit and 60.00 deactuation point degrees fahrenheit
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 8.3 amperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 35.00 actuation point degrees fahrenheit and 60.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts:
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 8.3 amperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 35.00 actuation point degrees fahrenheit and 60.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 240.0 ac at sea level first voltage
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 8.3 amperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 35.00 actuation point degrees fahrenheit and 60.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 240.0 ac at sea level first voltage Media For Which Designed:
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 8.3 amperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 35.00 actuation point degrees fahrenheit and 60.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 240.0 ac at sea level first voltage Media For Which Designed: Gas or liquid
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 8.3 amperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 35.00 actuation point degrees fahrenheit and 60.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 240.0 ac at sea level first voltage Media For Which Designed: Gas or liquid Style Designator:
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 8.3 amperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 35.00 actuation point degrees fahrenheit and 60.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 240.0 ac at sea level first voltage Media For Which Designed: Gas or liquid Style Designator: Disc w/flange
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 8.3 amperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 35.00 actuation point degrees fahrenheit and 60.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 240.0 ac at sea level first voltage Media For Which Designed: Gas or liquid Style Designator:

--

NSN 5930-00-855-4103

Thermostatic Switch - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A048b0