

View Online at <https://aerobasegroup.com/nsn/5930-00-855-5864>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Submersible

Overall Length:

1.340 inches

Overall Height:

2.980 inches

Overall Width:

0.910 inches

Bushing Length:

0.470 inches

Body Length:

1.340 inches

Body Width:

0.910 inches

Body Height:

1.100 inches

Actuator Style:

Round

Actuator Diameter:

0.420 inches

Actuator Height:

1.140 inches

Actuator Position-action Relationship:

Up position maintained and center position maintained

Actuator Position-locking Relationship:

Up position locked in and center position no locking action

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

1.370 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, single throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes inductive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 4.000 amperes lamp ac

Precious Material And Location:

Terminal surfaces silver

Test Data Document:

81349-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

4 screw

Specification Data:

96906-ms24659 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0