

View Online at <https://aerobasegroup.com/nsn/5930-00-856-1653>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Submersible

**Overall Length:**

1.340 inches

**Overall Height:**

3.005 inches

**Overall Width:**

0.910 inches

**Bushing Length:**

Between 0.450 inches and 0.490 inches

**Body Length:**

1.340 inches

**Body Width:**

0.910 inches

**Body Height:**

Between 1.080 inches and 1.120 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.400 inches and 0.440 inches

**Actuator Height:**

Between 1.135 inches and 1.145 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Actuator Position-locking Relationship:**

Up position locked out and down position no locking action and center position no locking action

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 4.000 amperes lamp ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0