NSN 5930-00-856-3852

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-856-3852

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
2.624 inches
Overall Height:
1.812 inches
Overall Width:
2.125 inches
First Flat Length:
0.500 inches single actuator
Flat Height:
0.210 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
0.937 inches single actuator
Unthreaded Mounting Hole Diameter:
0.187 inches single mounting facility
Individual Section Quantity:
2
Longest Horizontal Distance Between Mounting Centers:
1.437 inches single mounting facility
1.437 inches single mounting facility Longest Vertical Distance Between Mounting Centers:
Longest Vertical Distance Between Mounting Centers:
Longest Vertical Distance Between Mounting Centers: 1.750 inches single mounting facility
Longest Vertical Distance Between Mounting Centers: 1.750 inches single mounting facility Switch Contact Basic Design:
Longest Vertical Distance Between Mounting Centers: 1.750 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical
Longest Vertical Distance Between Mounting Centers: 1.750 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:
Longest Vertical Distance Between Mounting Centers: 1.750 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Bracket single mounting facility and unthreaded hole single mounting facility
Longest Vertical Distance Between Mounting Centers: 1.750 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Bracket single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts:
Longest Vertical Distance Between Mounting Centers: 1.750 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Bracket single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 30.0 dc at sea level
Longest Vertical Distance Between Mounting Centers: 1.750 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Bracket single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 30.0 dc at sea level Mounting Facility Pattern:
Longest Vertical Distance Between Mounting Centers: 1.750 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Bracket single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 30.0 dc at sea level Mounting Facility Pattern: Four position rectangular single mounting facility
Longest Vertical Distance Between Mounting Centers: 1.750 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Bracket single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 30.0 dc at sea level Mounting Facility Pattern: Four position rectangular single mounting facility Switch Actuator Indexing Position Quantity:
Longest Vertical Distance Between Mounting Centers: 1.750 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Bracket single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 30.0 dc at sea level Mounting Facility Pattern: Four position rectangular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator
Longest Vertical Distance Between Mounting Centers: 1.750 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Bracket single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 30.0 dc at sea level Mounting Facility Pattern: Four position rectangular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type:
Longest Vertical Distance Between Mounting Centers: 1.750 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Bracket single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 30.0 dc at sea level Mounting Facility Pattern: Four position rectangular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round, flatted single actuator
Longest Vertical Distance Between Mounting Centers: 1.750 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Bracket single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 30.0 dc at sea level Mounting Facility Pattern: Four position rectangular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round, flatted single actuator Terminal Type:
Longest Vertical Distance Between Mounting Centers: 1.750 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Bracket single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 30.0 dc at sea level Mounting Facility Pattern: Four position rectangular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round, flatted single actuator Terminal Type: Screw

Fixed stop single actuator

NSN 5930-00-856-3852

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0