

View Online at <https://aerobasegroup.com/nsn/5930-00-856-3855>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

4.500 inches

**First Flat Length:**

0.500 inches single actuator

**Flat Height:**

0.218 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

1.156 inches single actuator

**Overall Diameter:**

2.000 inches

**Unthreaded Mounting Hole Diameter:**

0.188 inches single mounting facility

**Individual Section Quantity:**

7

**Longest Horizontal Distance Between Mounting Centers:**

1.437 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.750 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

6 each section front

**Mounting Method:**

Threaded bushing single mounting facility

**Contact Voltage Rating In Volts:**

30.0 lowest dc voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load lowest dc voltage rating at sea level and 2.5 amperes inductive load lowest dc voltage rating at sea level

**Style Designator:**

Tap, circular, bushing mount

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0