

View Online at <https://aerobasegroup.com/nsn/5930-00-856-3855>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.500 inches

First Flat Length:

0.500 inches single actuator

Flat Height:

0.218 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.156 inches single actuator

Overall Diameter:

2.000 inches

Unthreaded Mounting Hole Diameter:

0.188 inches single mounting facility

Individual Section Quantity:

7

Longest Horizontal Distance Between Mounting Centers:

1.437 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.750 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

6 each section front

Mounting Method:

Threaded bushing single mounting facility

Contact Voltage Rating In Volts:

30.0 lowest dc voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load lowest dc voltage rating at sea level and 2.5 amperes inductive load lowest dc voltage rating at sea level

Style Designator:

Tap, circular, bushing mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0