

View Online at <https://aerobasegroup.com/nsn/5930-00-856-5068>

Thread Class:

2b 2nd mounting facility

Thread Length:

0.564 inches 1st mounting facility

Overall Height:

3.062 inches

Overall Width:

2.875 inches

Shaft Diameter:

0.250 inches single actuator

Individual Section Quantity:

3

Knob Manufacturer Code:

08538

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

18 each section front

Mounting Facility Circle Radius:

0.812 inches 2nd mounting facility

Mounting Method:

Threaded bushing 1st mounting facility

Features Provided:

Actuator knob and metallic inclosure

Thready Qty Per Inch (tpi):

32 2nd mounting facility

Thread Size:

0.375 inches 1st mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Rotor Through Connection Quantity:

1 each section

Mounting Facility Pattern:

Three position circular 2nd mounting facility

Switch Actuator Indexing Position Quantity:

18 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

20.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

3.0 amperes resistive load ac at sea level

Special Features:

Knob supplied with metal insert

Style Designator:

Tap, square frame

Thread Series Designator:

Unef 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0