NSN 5930-00-856-5068

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-856-5068

Thread Class: 2b 2nd mounting facility Thread Length: 0.564 inches 1st mounting facility **Overall Height:** 3.062 inches **Overall Width:** 2.875 inches **Shaft Diameter:** 0.250 inches single actuator **Individual Section Quantity:** 3 **Knob Manufacturer Code:** 08538 **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 18 each section front **Mounting Facility Circle Radius:** 0.812 inches 2nd mounting facility **Mounting Method:** Threaded bushing 1st mounting facility **Features Provided:** Actuator knob and metallic inclosure Thready Qty Per Inch (tpi): 32 2nd mounting facility **Thread Size:** 0.375 inches 1st mounting facility **Contact Voltage Rating In Volts:** 115.0 ac at sea level **Rotor Through Connection Quantity:** 1 each section **Mounting Facility Pattern:** Three position circular 2nd mounting facility **Switch Actuator Indexing Position Quantity:** 18 single actuator **Shaft Type:** Round single actuator

Terminal Type: Tab, solder lug

NSN 5930-00-856-5068

Rotary Switch - Page 2 of 2



Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
20.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
3.0 amperes resistive load ac at sea level
Special Features:
Knob supplied with metal insert
Style Designator:
Tap, square frame
Thread Series Designator:
Unef 1st mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0