## NSN 5930-00-856-5192

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-856-5192

**Thread Class:** 

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

**Hazardous Locations/environmental Protection:** 

Dustproof

**Overall Length:** 

1.230 inches

**Shaft Diameter:** 

0.125 inches single actuator

**Shaft Length:** 

0.610 inches single actuator

**Overall Diameter:** 

0.500 inches

**Individual Section Quantity:** 

,

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section front

**Throw Quantity:** 

6 single section front

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:** 

250.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

6 single actuator

**Shaft Type:** 

Round single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Makes before breaks single section front

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

**Contact Load Current Rating:** 

0.5 amperes resistive load dc at sea level

## NSN 5930-00-856-5192

Rotary Switch - Page 2 of 2



•	_		
Style	1)69	เตทร	ntor.
01,10	-	9	

Snap or line

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0