NSN 5930-00-856-5459



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-856-5459 **Body Style: Bushing mounted Overall Length:** 2.858 inches **Overall Height:** 2.180 inches **Overall Width:** 0.695 inches **Bushing Length:** 0.750 inches **Body Length:** 1.040 inches **Body Width:** 0.695 inches **Body Height:** 2.180 inches **Case Material:** Metal **Actuator Style:** Roller plunger **Actuator Free Position Height:** 1.498 inches **Actuator Roller Diameter:** 0.430 inches **Actuator Roller Width:** 0.040 inches **Maximum Voltage Rating In Volts:** 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

6.0 ounces

Switch Actuating Force:

Between 10.0 ounces and 20.0 ounces

NSN 5930-00-856-5459

Sensitive Switch - Page 2 of 2



Δ	ctu	ator	·Mc	WA	mar	١+.
н	CLU	alui	IVIC	vei	пег	H.

Between 0.065 pretravel inches and 0.188 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0