NSN 5930-00-856-5535

Rotary Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-00-856-5535 |
|---|
| Thread Class: |
| 2b single mounting facility |
| Hazardous Locations/environmental Protection: |
| Dustproof |
| Overall Length: |
| 2.281 inches |
| Overall Height: |
| 2.500 inches |
| First Flat Length: |
| 0.437 inches single actuator |
| Flat Height: |
| 0.218 inches single actuator |
| Shaft Diameter: |
| 0.250 inches single actuator |
| Shaft Length: |
| 0.687 inches single actuator |
| Individual Section Quantity: |
| 1 |
| Knob Manufacturer Code: |
| 82121 |
| Knob Manufacturer Part Number: |
| 8204-7 |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 single section rear |
| Throw Quantity: |
| 2 single section rear |
| Mounting Facility Circle Radius: |
| 1.312 inches single mounting facility |
| Mounting Method: |
| Bracket single mounting facility and threaded hole single mounting facility |
| Features Provided: |
| Actuator knob |
| Thready Qty Per Inch (tpi): |
| 24 single mounting facility |
| Thread Size: |
| 0.190 inches single mounting facility |
| Contact Voltage Rating In Volts: |

125.0 ac at sea level

Mounting Facility Pattern:

Four position circular single mounting facility

NSN 5930-00-856-5535Rotary Switch - Page 2 of 2



| Switch Actuator Indexing Position Quantity: |
|---|
| 2 single actuator |
| Shaft Type: |
| Round, flatted, threaded hole single actuator |
| Terminal Type: |
| Tab w/screw |
| Contact Switching Action: |
| Breaks before makes single section rear |
| Switch Actuator Positioning Increment: |
| 90.0 degrees single actuator |
| Contact Load Current Rating: |
| 10.0 amperes resistive load ac at sea level |
| Style Designator: |
| Tap, circuit selector |
| Thread Series Designator: |
| Unc single mounting facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |

No Fiig: A052b0