NSN 5930-00-856-7196

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-856-7196 **Thread Class:** 2b single mounting facility **Overall Length:** 4.594 inches **Overall Height:** 1.750 inches **Overall Width:** 1.750 inches First Flat Length: 0.250 inches single actuator Flat Height: 0.218 inches single actuator **Shaft Diameter:** 0.249 inches single actuator **Shaft Length:** 0.750 inches single actuator **Distance Between Mounting Facility Centers:** 1.375 inches single mounting facility **Individual Section Quantity: Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 4 each section front **Throw Quantity:** 4 each section front **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.138 inches single mounting facility **Contact Voltage Rating In Volts:** 110.0 ac at sea level **Mounting Facility Pattern:** Two position in-line single mounting facility **Switch Actuator Indexing Position Quantity:** 4 single actuator **Shaft Type:** Round, flatted single actuator

Terminal Type: Tab, solder lug

NSN 5930-00-856-7196

Rotary Switch - Page 2 of 2



| Contact Switching Action: |
|--|
| Breaks before makes each section front |
| Switch Actuator Positioning Increment: |
| 22.5 degrees single actuator |
| Switch Actuator Stop Device Type: |
| Fixed stop single actuator |
| Contact Load Current Rating: |
| 5.0 amperes resistive load ac at sea level |
| Precious Material And Location: |
| Contacts silver |
| Precious Material: |
| Silver |
| Style Designator: |
| Tap, square frame |
| Thread Series Designator: |
| Unc single mounting facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A052b0