

View Online at <https://aerobasegroup.com/nsn/5930-00-857-9916>

**Overall Length:**

8.625 inches

**First Flat Length:**

0.531 inches single actuator

**Flat Height:**

0.219 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.906 inches single actuator

**Overall Diameter:**

4.250 inches

**Unthreaded Mounting Hole Diameter:**

0.190 inches single mounting facility

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Slotted bushing at 6: 00 o'clock

**Operating Temperature Range:**

-20.0/+65.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

6 each section rear

**Mounting Facility Circle Radius:**

1.188 inches single mounting facility

**Mounting Method:**

Bracket single mounting facility

**Contact Voltage Rating In Volts:**

300.0 ac at sea level

**Shaft Flat/slot Angular Location:**

0.0 degrees from nonturn device single actuator

**Mounting Facility Pattern:**

Three position circular single mounting facility

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

50.0 amperes resistive load ac at sea level

**Style Designator:**

Circular wafer, bushing mount

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0