

View Online at <https://aerobasegroup.com/nsn/5930-00-858-9320>

Thread Class:

2b 2nd mounting facility

Thread Length:

0.313 inches 1st mounting facility

Overall Length:

3.910 inches

Overall Height:

4.125 inches

Overall Width:

4.125 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.687 inches single actuator

Nonturn Device Radius:

0.500 inches at 12: 00 o'clock

Distance Between Mounting Facility Centers:

1.375 inches 2nd mounting facility

Individual Section Quantity:

4

Nonturn Device Type:

Tab at 12: 00 o'clock

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

16 each section front

Mounting Method:

Threaded bushing 1st mounting facility

Thready Qty Per Inch (tpi):

32 2nd mounting facility

Thread Size:

0.375 inches 1st mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Mounting Facility Pattern:

Two position in-line 2nd mounting facility

Switch Actuator Indexing Position Quantity:

16 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

22.5 degrees single actuator

Detent Rotational Torque Range:

+10.000/+12.000 inch-pounds single actuator

Contact Load Current Rating:

2.0 amperes resistive load dc at sea level

Style Designator:

Square wafer, panel mount

Thread Series Designator:

Unef 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0