## NSN 5930-00-858-9780

Pressure Switch - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5950-00-656-9760
Overall Length:
1.750 inches
Outside Diameter:
0.195 inches all connections and 0.205 inches all connections
Overall Height:
0.478 inches
Overall Width:
1.312 inches
Body Length:
1.000 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Longest Horizontal Distance Between Mounting Centers:
0.719 inches
Longest Vertical Distance Between Mounting Centers:
0.719 inches
Pressure Switch Type:
Differential
Mounting Method:
Base and unthreaded hole
Contact Action Stimulus:
Increase
Proof Pressure:
8.00 pounds per square inch gage
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, double make, momentary action
Terminal Type:
Quick disconnect, male
Contact Load Current Rating:
10.0 milliamperes resistive load second voltage
Contact Adjustability:
Actuation point not adjustable
Contact Stimulus Rating:
3.00 actuation point inches of water
Contact Voltage Rating In Volts:
30.0 dc at sea level second voltage
Pressure Connector Type:
Barbed, unthreaded external all connections
Media For Which Designed:

Gas

## **NSN 5930-00-858-9780**Pressure Switch - Page 2 of 2



<b>Precious Material And Location:</b>
Contacts gold
Precious Material:
Gold
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0