

View Online at <https://aerobasegroup.com/nsn/5930-00-859-1273>

Thread Class:

2a single mounting facility

Thread Length:

0.240 inches single mounting facility and 0.260 inches single mounting facility

Overall Length:

Between 1.989 inches and 2.009 inches

Overall Height:

Between 1.521 inches and 1.541 inches

Overall Width:

Between 1.396 inches and 1.416 inches

First Flat Length:

0.240 inches single actuator and 0.260 inches single actuator

Flat Height:

0.209 inches single actuator and 0.229 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.740 inches single actuator and 0.760 inches single actuator

Nonturn Device Radius:

0.521 inches at 9:00 o'clock and 0.541 inches at 9:00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Tab at 9:00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 2nd section front

Throw Quantity:

6 3rd section rear

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

105.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes 2nd section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0