

View Online at <https://aerobasegroup.com/nsn/5930-00-859-1273>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.240 inches single mounting facility and 0.260 inches single mounting facility

**Overall Length:**

Between 1.989 inches and 2.009 inches

**Overall Height:**

Between 1.521 inches and 1.541 inches

**Overall Width:**

Between 1.396 inches and 1.416 inches

**First Flat Length:**

0.240 inches single actuator and 0.260 inches single actuator

**Flat Height:**

0.209 inches single actuator and 0.229 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.250 inches single actuator

**Shaft Length:**

0.740 inches single actuator and 0.760 inches single actuator

**Nonturn Device Radius:**

0.521 inches at 9:00 o'clock and 0.541 inches at 9:00 o'clock

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Tab at 9:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

3 2nd section front

**Throw Quantity:**

6 3rd section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

105.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

12 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes 2nd section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0