

View Online at <https://aerobasegroup.com/nsn/5930-00-859-1455>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

6.060 inches

**Overall Height:**

6.000 inches

**Overall Width:**

7.500 inches

**Unthreaded Mounting Hole Diameter:**

0.530 inches single mounting facility

**Distance Between Mounting Facility Centers:**

6.380 inches single mounting facility

**Individual Section Quantity:**

1

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Contact Voltage Rating In Volts:**

440.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Two position in-line single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

6.0 amperes resistive load lowest ac voltage rating at sea level

**Special Features:**

Bracket for two actuator position reads on emer/stop

**Style Designator:**

In-line, cam actuated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0