NSN 5930-00-859-3480

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-859-3480

Thread Class: 2a single mounting facility **Thread Length:** 0.250 inches single mounting facility **Overall Length:** 1.187 inches **Overall Height:** 1.000 inches **Overall Width:** 0.937 inches **Shaft Diameter:** 0.125 inches single actuator **Shaft Length:** 0.437 inches single actuator **Nonturn Device Radius:** 0.375 inches at 3: 00 o'clock **Individual Section Quantity:** 1 **Nonturn Device Type:** Tab at 3: 00 o'clock **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.250 inches single mounting facility **Contact Voltage Rating In Volts:** 6.0 dc at sea level Shaft Flat/slot Angular Location: 90.0 degrees from nonturn device single actuator **Switch Actuator Indexing Position Quantity:** 3 single actuator **Shaft Type:** Round, slotted single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:** 30.0 degrees single actuator **Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level

NSN 5930-00-859-3480

Rotary Switch - Page 2 of 2



Sty	عا	D	26	ia	n	a	ŧ٥	r	
JLY	ı	יש	ငၥ	щ		а	ιv	ш	

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0