## NSN 5930-00-860-1230

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-860-1230

### First Flat Length:

0.125 inches single actuator

### **Shaft Diameter:**

0.250 inches single actuator

### **Shaft Length:**

1.000 inches single actuator

### **Unthreaded Mounting Hole Diameter:**

0.187 inches single mounting facility

### **Individual Section Quantity:**

4

### **Longest Horizontal Distance Between Mounting Centers:**

1.125 inches single mounting facility

### **Longest Vertical Distance Between Mounting Centers:**

0.187 inches single mounting facility

### **Switch Contact Basic Design:**

Nonpile-up symmetrical

### **Pole Quantity:**

1 each section front

### **Throw Quantity:**

1 each section front

### **Mounting Method:**

Base single mounting facility

### **Contact Voltage Rating In Volts:**

600.0 ac at sea level

### **Mounting Facility Pattern:**

Four position rectangular single mounting facility

### **Switch Actuator Indexing Position Quantity:**

2 single actuator

#### **Shaft Type:**

Round, flat, undercut single actuator

### **Terminal Type:**

Tab w/screw

### **Contact Switching Action:**

Breaks before makes each section front

### **Switch Actuator Positioning Increment:**

90.0 degrees single actuator

### **Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level

### Shelf Life:

N/a

### **Unit Of Measure:**

--

# NSN 5930-00-860-1230

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0