

View Online at <https://aerobasegroup.com/nsn/5930-00-860-4148>

Thread Class:

2a 1st mounting facility 2b 2nd mounting facility

Thread Length:

0.312 inches 1st mounting facility

Overall Length:

2.625 inches

Overall Height:

1.750 inches

Overall Width:

1.750 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.688 inches single actuator

Nonturn Device Radius:

0.500 inches at 6: 00 o'clock

Distance Between Mounting Facility Centers:

1.376 inches 2nd mounting facility

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 6: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

3 each section rear

Mounting Method:

Threaded bushing 1st mounting facility threaded hole 2nd mounting facility

Thready Qty Per Inch (tpi):

32 2nd mounting facility

Thread Size:

0.375 inches 1st mounting facility 0.138 inches 2nd mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Mounting Facility Pattern:

Two position in-line 2nd mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

2.0 amperes resistive load ac at sea level

Style Designator:

Tap, square frame

Thread Series Designator:

Unef 1st mounting facilityunc 2nd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0