

View Online at <https://aerobasegroup.com/nsn/5930-00-862-0263>

Thread Class:

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

Overall Length:

2.125 inches

Overall Height:

2.000 inches

Overall Width:

2.000 inches

First Flat Length:

0.500 inches single actuator

Shaft Diameter:

0.251 inches single actuator

Shaft Length:

0.875 inches single actuator

Nonturn Device Radius:

0.531 inches at 12: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

7 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Shaft Flat/slot Angular Location:

45.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

7 single actuator

Shaft Type:

Round, v flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

22.5 degrees single actuator

Detent Rotational Torque Range:

+30.000/+198.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Style Designator:

Square wafer, panel mount

Test Data Document:

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0