NSN 5930-00-862-7461

400.00 differential point pounds per square inch

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-862-7461

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
4.562 inches
Overall Height:
6.750 inches
Body Length:
2.937 inches
Body Height:
4.375 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Distance Between Mounting Facility Centers:
2.000 inches
Pressure Switch Type:
Gage
Operating Tempurature Rating:
Between -67.0 degrees fahrenheit and 125.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
1.0 amperes inductive load single voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+2850.00/+3000.00 actuation point pounds per square inch and +2450.00/+3000.00 deactuation point pounds per square inch
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Stimulus Rating:

NSN 5930-00-862-7461

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts: 24.0 dc at sea level single voltage Pressure Connector Type: Plain, threaded internal single connection Media For Which Designed: Liquid Style Designator: Rectangular Thread Series Designator: Npt single pressure connection Shelf Life: N/a Unit Of Measure: ---

Demilitarization:

No Fiig: A048b0