

View Online at <https://aerobasegroup.com/nsn/5930-00-862-7461>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.562 inches

Overall Height:

6.750 inches

Body Length:

2.937 inches

Body Height:

4.375 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

2.000 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -67.0 degrees fahrenheit and 125.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

1.0 amperes inductive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+2850.00/+3000.00 actuation point pounds per square inch and +2450.00/+3000.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

400.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

24.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0