NSN 5930-00-863-5295

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-863-5295

· · · · · · · · · · · · · · · · · · ·
Hazardous Locations/environmental Protection:
Salt spray resistant
Overall Length:
4.109 inches
Overall Height:
0.938 inches
Overall Width:
0.562 inches
Unthreaded Mounting Hole Diameter:
0.156 inches single mounting facility
Individual Section Quantity:
2
Operating Tempurature Range:
-40.0/+71.0 degrees celsius
Switch Contact Basic Design:
Pile-up
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Pile-up Contact Form Arrangement:
1c each switch each section in-line
Contact Voltage Rating In Volts:
115.0 ac at sea level
Switch Actuator Indexing Position Quantity:
2 single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section in-line
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
3.0 amperes resistive load ac at sea level
Style Designator:
In-line, pile-up, panel mount
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5930-00-863-5295 Rotary Switch - Page 2 of 2



Fiig:

A052b0