

View Online at <https://aerobasegroup.com/nsn/5930-00-864-0637>

Thread Length:

0.375 inches single mounting facility

Overall Length:

2.500 inches

Overall Height:

1.312 inches

Overall Width:

1.250 inches

First Flat Length:

0.313 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.875 inches single actuator

Individual Section Quantity:

2

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

60.0 degrees single actuator

Special Features:

For circuits requiring higher ratings, silver-alloy and high-temperature contacts will break current on a resistive load of 2 ampere at 28 volts d.C. Or 1 ampere at 110 volts a.C with a reliable life of 50, 000 operations

Style Designator:

Circular wafer, bushing mount

Supplementary Features:

1 ampere at 28 volts d.C. Or .5 ampere at 110 volts a.C. Dielectric constant 5.58, dielectric loss factor .00419, dissipation factor .00075

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0