

View Online at <https://aerobasegroup.com/nsn/5930-00-864-0637>

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

2.500 inches

**Overall Height:**

1.312 inches

**Overall Width:**

1.250 inches

**First Flat Length:**

0.313 inches single actuator

**Flat Height:**

0.219 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.875 inches single actuator

**Individual Section Quantity:**

2

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

60.0 degrees single actuator

**Special Features:**

For circuits requiring higher ratings, silver-alloy and high-temperature contacts will break current on a resistive load of 2 ampere at 28 volts d.C. Or 1 ampere at 110 volts a.C with a reliable life of 50, 000 operations

**Style Designator:**

Circular wafer, bushing mount

**Supplementary Features:**

1 ampere at 28 volts d.C. Or .5 ampere at 110 volts a.C. Dielectric constant 5.58, dielectric loss factor .00419, dissipation factor .00075

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0