

View Online at <https://aerobasegroup.com/nsn/5930-00-865-0039>

**Thread Length:**

0.437 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof and explosion proof

**First Flat Length:**

0.375 inches single actuator

**Flat Height:**

0.212 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.937 inches single actuator

**Individual Section Quantity:**

5

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

6 each section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load ac at sea level

**Special Features:**

Corrosion, humidity, and fungus proof

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0