

View Online at <https://aerobasegroup.com/nsn/5930-00-865-1329>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

0.470 inches

Body Length:

1.340 inches

Body Width:

0.910 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.680 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 30.0 dc

Mounting Surface To Terminal End Distance:

1.350 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Rfi shielding

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive dc and 15.000 amperes inductive dc and 5.000 amperes lamp dc and 15.000 amperes resistive ac and 11.000 amperes inductive ac and 4.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0