## NSN 5930-00-865-6093

**Hazardous Locations/environmental Protection:** 

Push-pull Switch - Page 1 of 2

**Body Style:** 

Dustproof

Bushing mounted

Overall Length:



View Online at https://aerobasegroup.com/nsn/5930-00-865-6093

1.080 inches
Overall Height:
2.620 inches
Overall Width:
1.440 inches
Bushing Length:
0.310 inches
Body Length:
1.080 inches
Body Width:
0.750 inches
Body Height:
1.870 inches
Case Material:
Metal
Actuator Style:
Round, threaded
Actuator Height:
0.500 inches
Maximum Voltage Rating In Volts:
32.0 dc
Inclosure Type:
Inclosure Type: Fully enclosed
Fully enclosed
Fully enclosed  Mounting Method:
Fully enclosed  Mounting Method:  Threaded bushing
Fully enclosed  Mounting Method: Threaded bushing  Thread Size:
Fully enclosed  Mounting Method: Threaded bushing  Thread Size: 0.375 inches
Fully enclosed  Mounting Method: Threaded bushing  Thread Size: 0.375 inches  Nonpile-up Contact Arrangement:
Fully enclosed  Mounting Method: Threaded bushing  Thread Size: 0.375 inches  Nonpile-up Contact Arrangement: 2 pole, single throw, both positions maintained single switch unit
Fully enclosed  Mounting Method: Threaded bushing  Thread Size: 0.375 inches  Nonpile-up Contact Arrangement: 2 pole, single throw, both positions maintained single switch unit  Contact Load Current Rating At Maximum Rated Voltage:
Fully enclosed  Mounting Method: Threaded bushing  Thread Size: 0.375 inches  Nonpile-up Contact Arrangement: 2 pole, single throw, both positions maintained single switch unit  Contact Load Current Rating At Maximum Rated Voltage: 15.000 amperes resistive dc
Fully enclosed  Mounting Method: Threaded bushing  Thread Size: 0.375 inches  Nonpile-up Contact Arrangement: 2 pole, single throw, both positions maintained single switch unit  Contact Load Current Rating At Maximum Rated Voltage: 15.000 amperes resistive dc  Special Features:
Fully enclosed  Mounting Method: Threaded bushing  Thread Size: 0.375 inches  Nonpile-up Contact Arrangement: 2 pole, single throw, both positions maintained single switch unit  Contact Load Current Rating At Maximum Rated Voltage: 15.000 amperes resistive dc  Special Features:  Plastic ivory colored screw on actuator knob; inscribed lights furnished with item
Fully enclosed  Mounting Method: Threaded bushing  Thread Size: 0.375 inches  Nonpile-up Contact Arrangement: 2 pole, single throw, both positions maintained single switch unit  Contact Load Current Rating At Maximum Rated Voltage: 15.000 amperes resistive dc  Special Features: Plastic ivory colored screw on actuator knob; inscribed lights furnished with item  Precious Material And Location:
Fully enclosed  Mounting Method: Threaded bushing  Thread Size: 0.375 inches  Nonpile-up Contact Arrangement: 2 pole, single throw, both positions maintained single switch unit  Contact Load Current Rating At Maximum Rated Voltage: 15.000 amperes resistive dc  Special Features: Plastic ivory colored screw on actuator knob; inscribed lights furnished with item  Precious Material And Location: Headlamp terminal rivets and contacts silver

## NSN 5930-00-865-6093

Push-pull Switch - Page 2 of 2



Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0