# NSN 5930-00-866-8586

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-866-8586

#### Thread Length:

0.430 inches single mounting facility

# Hazardous Locations/environmental Protection:

Dustproof

# First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.210 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.800 inches single actuator

#### Individual Section Quantity:

8

#### Switch Contact Basic Design:

# Nonpile-up nonsymmetrical

**Pole Quantity:** 

1 each section front

### **Throw Quantity:**

11 each section front

#### Mounting Method:

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

11 single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes each section front

#### Switch Actuator Positioning Increment:

22.5 degrees single actuator

#### **Contact Load Current Rating:**

5.0 amperes resistive load ac at sea level

#### **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5930-00-866-8586

Rotary Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A052b0

